



Manufacturer certificate:

AUTOPSTENHOJ 4-ram lift 4.55 KA1550/3000 F480

We hereby confirm that our AUTOPSTENHOJ in-ground wheel alignment lift 4.55 F480 KA 1550/3000 complies with all demands and requirements of the BMW Group, in ref. to manual version 3.2 of December 13th 2016 – „Workshop planning – automotive lifts“.



A 4-ram lift 4.55 KA1550/3000 F480 for BMW and MINI consists of the following components:

Item number	Description
21114	Set of platforms 4.55 F 480 KA 1550/3000
10299	Hydraulic unit QL 4.55, cyl. Ø 140, lift 1875 KA 1550 / KA 3000
12040	Ecological hydraulic liquid, 20 l
12310	Cassette set QL 4.55 / 4.65
12461	B, BMW-approvals and colour - grey RAL 7016

For recession (also 2 x item number 21078 or 1 x item number 21078 and 1 x item number 1074):futhermore

21078	Automatically rising stoppers QL 4.65 (1 Set = 2 pieces) for recessed installation
21074	Fixed stoppers, QL 4.65, 1 Set = 2 pieces, for recessed/on-floor installation
For on-floor installation (due to the total length > 5700 mm, according to above mentioned specification sheet not allowed):	
21095	1400 mm drive-on ramps, 8° (1 set = 2 pieces) QL 4.55/65, for surface-mounting
21074	Stoppers, QL 4.65, 1 Set = 2 pieces, for recessed/on floor installation
Recommended accessories	
11073	Cable set QL 4.55 / 4.65
12420	Surcharge for zinc coating of platforms QL 4.55 / 4.65
12942	LED lighting set, 3 modules per platform
21089	Air hydraulic scissor jack, 2,6 t, innovative air connection incl.
20547	Side slip plates autop Premium (1 set = 2 pieces) comply with BMW demands of $\pm 56\text{mm}$, $\pm 6,5^\circ$

Other optional extras available on request.

Rheine, 06.07.2017

Best Regards,
 AUTOPSTENHOJ
 autop Maschinenbau GmbH
 STENHØJ A/S

Martin Richters
 Product Manager, Lifts